

Wires with hook

Product description:

Element is made of galvanized steel wire, diameter 4.00 mm. Used to hang drywall or cassette design to lower the ceilings. Hook forms one side and is used for attachment to the solid construction of buildings. Quickhanger or butterfly spring can be mounted on the straight end.



Range of usage:

The product is used for fixing the drywall elements into solid structures of buildings. It is used to reduce the ceiling in plasterboard or cassette structures.

Characteristics:

Material	Drawn wire
Coating	Zinc – min Z100 (ČSN EN 10327)
Thickness	4.00 mm (ČSN EN 10143)
Reaction to fire	Class A1 (EN 14195)
Durability	Class B
Hazardous substance	NPD

Product variability:

Code	Name	Load	Pack	Weight
TMD-2927 (1.348139 T)	Wire with eyelet 6 mm - 0125 mm	0,50 kN	100 pcs	0,0142 kg
TMD-1274 (1.348140 T)	Wire with eyelet 6 mm - 0250 mm	0,50 kN	100 pcs	0,0258 kg
TMD-2824 (1.348141 T)	Wire with eyelet 6 mm - 0375 mm	0,50 kN	100 pcs	0,0375 kg
TMD-2831 (1.348142 T)	Wire with eyelet 6 mm - 0500 mm	0,50 kN	100 pcs	0,0491 kg
TMD-2905 (1.348143 T)	Wire with eyelet 6 mm - 0750 mm	0,50 kN	100 pcs	0,0723 kg
TMD-2988 (1.348144 T)	Wire with eyelet 6 mm - 1000 mm	0,50 kN	100 pcs	0,0958 kg
TMD-3012 (1.348145 T)	Wire with eyelet 6 mm - 1200 mm	0,50 kN	100 pcs	0,1142 kg
TMD-2938 (1.348146 T)	Wire with eyelet 6 mm - 1500 mm	0,50 kN	100 pcs	0,1422 kg
TMD-3044 (1.348147 T)	Wire with eyelet 6 mm - 2000 mm	0,50 kN	100 pcs	0,1887 kg
TMD-0926 (1.348138.1,5,2)	Wire with eyelet 6 mm - 2500 mm	0,50 kN	100 pcs	0,2353 kg
TMD-2218 (1.348135,5,1 T)	Wire with eyelet 6 mm - 3000 mm	0,50 kN	100 pcs	0,2818 kg

Real weight may vary in range of +/-5% according to ČSN EN10143



Wires with hook

Mounting:

Mount the wire to the ceiling using hanger peg. Another possibility is to attach the wire to the beam clamp, which is attached to a steel girder. Put a flat side to the double spring clip or single clip which is part of the product intended for subsequent hanging profile which allows quick and easy leveling construction.


Packaging:

The wires up to length of 500 mm are packed by 100 pcs in carton box. Longer variations are packed by 100 pcs with cable tie. Every dimension is labeled with identification tag.

Recommended storage:

The product is required to store in dry and temperate environment in order to prevent condensation on the surface of the product and damage to the packaging.

Technical drawing:



Code	Product	Weight	A
TMD-2927	Wire with hook – 0125 mm	0,0142 kg	125 mm
TMD-1274	Wire with hook – 0250 mm	0,0258 kg	250 mm
TMD-2824	Wire with hook – 0375 mm	0,0375 kg	375 mm
TMD-2831	Wire with hook – 0500 mm	0,0491 kg	500 mm
TMD-2905	Wire with hook – 0750 mm	0,0723 kg	750 mm
TMD-2988	Wire with hook – 1000 mm	0,0958 kg	1000 mm
TMD-3012	Wire with hook – 1200 mm	0,1142 kg	1200 mm
TMD-2938	Wire with hook – 1500 mm	0,1422 kg	1500 mm
TMD-3044	Wire with hook – 2000 mm	0,1887 kg	2000 mm
TMD-0926	Wire with hook – 2500 mm	0,2353 kg	2500 mm
TMD-2218	Wire with hook – 3000 mm	0,2818 kg	3000 mm

