

Chevron hangers PC

Product description:

The chevron hanger is used as mounting element for anchoring the drywall steel profiles PC into the wooden construction of the buildings in a horizontal or sloping system. It is produced by compression molding of a rolled, galvanized metal sheet with thickness of 0.80 mm and 1.00 mm. It is screwed into the sides of a chevron or chalets with flat headed screws. The installation is done by snapping into profile after screwing into the construction.



Range of usage:

The product is used for metal profiles mounting into wooden construction of the buildings in a horizontal or sloping system.

Characteristics:

| | |
|----------------------------|----------------------------------|
| Material | Rolled sheet DX51 |
| Coating | Zinc – min Z100 (ČSN EN 10327) |
| Thickness | 0.80 mm / 1.00 mm (ČSN EN 10143) |
| Reaction to fire | Class A1 (EN 14195) |
| Durability | Class B |
| Hazardous substance | NPD |

Product variability:

| Code | Name | Load | Pack | Weight |
|--------------------------|--|---------|---------|-----------|
| TMD-3905 (1.348182 T) | Chevron hanger PC 60/27 - rounded 200 mm | 0,40 kN | 100 pcs | 0,0362 kg |
| TMD-3906 (1.348183 T) | Chevron hanger PC 60/27 - rounded 300 mm | 0.40 kN | 100 pcs | 0,0850 kg |

Real weight may vary in range of +/-5% according to ČSN EN10143

Mounting:

Mount the chevron hanger into the wooden structure with self-tapping screws at correct position from the ceiling and snap the PC profile onto the hanger.

Packaging:

The hangers are packed by 100 pcs in carton box. Every dimension is labeled with identification tag.

Recommended storage:

The product is required to store in dry and temperate environment in order to prevent condensation on the surface of the product and damage to the packaging.



Chevron hangers PC

Technical drawing:

