

Cross connector PC

Product description:

The cross connector bended is used for mounting the two-level, cross-raster grid created from plasterboard and steel profiles PC. It is produced by compression molding of the rolled galvanized steel sheet of a thickness 1.00 mm. The bracket is provided with elements to define volition between the connected profiles. To simplify the work, it is supplied already in a bent state.



Range of usage:

The product is used for connecting two PC 60x27 profiles in cross-raster grid of drywall construction.

Characteristics:

Identification code	1.348184 T
Order code	TMD-3907
Name	Cross connector PC 60/27 - bended
Packaging	100 pc (390x230x170 mm)
Weight	0.0433 kg
Permissible load	0,50 kN
Material	Rolled sheet, drawn steel
Thickness	1.00 mm (ČSN EN 10143)
Reaction to fire	Class A1 (EN 14195)
Durability	Class B
Hazardous substance	NPD

Real weight may vary in range of +/-5% according to ČSN EN10143

Mounting:

The connector is anchored by fitting over top profile (PC 60x27) and then pushing it into the bottom profile until it clicks.

Packaging:

The connector is packed by 100 pcs in carton box. Every dimension is labeled with identification tag.

Recommended storage:

The product is required to store in dry and temperate environment in order to prevent condensation on the surface of the product and damage to the packaging.



TECHNICAL SHEET

No: T-20-0054

Cross connector PC

Technical drawing:

